

STANDARD MASTER FLASH®



ISO Quality, Price & Availability / TWO COMPOUNDS / 11 SIZES

ADVANCED OZONE RESISTANCE tested to...	EPDM 70 hour @ 500 pphm	SILICONE 70 hour @ 500 pphm
HIGH TEMPERATURE RESISTANCE Tested to	Intermittent	+135°C (+275°F)
	Continuous	+100°C (+212°F)
LOW TEMPERATURE RESISTANCE tested to...	-55°C (-67°F)	-74°C (-101°F)
COMPRESSION SET minimum...	25%	50%

*Complete specification data and testing methods are available upon request

✓ Design Excellence

Aztec's flexible design meets all roofing needs. Sleeve flexibility accommodates vibration and pipe movement caused by expansion - contraction. The soft aluminum base easily conforms to most metal roof profiles.

✓ Weather Protection

Made of E.P.D.M or Silicone, these flashings are compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light.



✓ Base Flexibility


The base is designed to form a seal on most panel configurations and roof pitches regardless of pipe location.

✓ Easy On-Site Customization


Fast one piece construction allows for easy on-site installation in usually 5 minutes.




1 Choose Pipe Opening and Trim




2 Slide Over Pipe



3 Form to Roof Profile



4 Apply Sealant



5 Fasten to Complete



Master Flash® was used to create a new engineering standard for profiled roofing by the International Association of Plumbing and Mechanical Officials (for the Uniform Plumbing Code) and remains the only product listed. These products are also listed for use with Type B vents.

The addition of fire retarding agents milled directly into the rubber compound created a self extinguishing feature which enables it to be used with type "B" vents. Listed with IAPMO certification No. 3121